

IMAGE SIGNAL CODING DEVICE AND IMAGE SIGNAL DECODING DEVICE

Publication number: JP4311195 (A)

Publication date: 1992-11-02

Inventor(s): FUKUDA HIROYUKI +

Applicant(s): OLYMPUS OPTICAL CO +

Classification:

- **International:** **G06T9/00; H04N1/41; H04N11/04; H04N7/30; G06T9/00; H04N1/41; H04N11/04; H04N7/30; (IPC1-7): G06F15/86; H04N1/41; H04N11/04; H04N7/133**

- **European:**

Application number: JP19910077975 19910410

Priority number(s): JP19910077975 19910410


Also published as:

 JP3081658 (B2)

Abstract of JP 4311195 (A)

PURPOSE:To offer an image signal coding/decoding device capable of suppressing a color difference signal mosquito noise generated by the coding/decoding of an image signal.

CONSTITUTION:The coding/decoding device is constituted so that an input image signal is separated into a brightness signal Y and a color difference signal Cr by an Y/C separating circuit 10, the signal Y is compared with a prescibe threshold by a brightness signal picture element judging circuit 11, after distortion suppressing processing for easing a sudden change in the color difference signal judged as 'saturated picture element', the processed data are outputted as coded image data and decoded by a decoding circuit 15, the decoded brightness signal is led to a brightness signal picture element judging circuit 16 to judge 'saturated picture element'; the value of the 'saturated picture element' color difference signal is changed to '0' by a color difference signal changing circuit 17, the changed color difference signal and the brightness signal from the decoding circuit 15 are synthesized by an Y/C synthesizing circuit 18, and the synthesized signal is outputted as a reproduced signal.



.....
Data supplied from the **espacenet** database — Worldwide